

BatesField GPU - Diesel Series

DC OUTPUT VOLTAGE: Standard with 28.5VDC outlet with 12VDC available for \$150.

Series	DC Output Amperage
3000	2,600 cranking amps; 300 amps for pre-start operations
2400	2,540 cranking amps; 240 amps for pre-start operations
1800	2,480 cranking amps; 180 amps for pre-start operations
1200	2,420 cranking amps; 120 amps for pre-start operations

DC OUTPUT CABLE: 20' of 4/0 cable with 3 pin aircraft plug standard except for 1200 series where 15' of 2/0 cable is standard with available upgrade to 4/0 cable in lieu of 2/0 cable for \$475.

AC INPUT CABLE: 50' with customer providing plug for hangar use if hangar power is used.

PANEL METERS: AC Volt meter, Hours meter, and State of Charge meter standard on all series. DC-Volt and DC-Amp standard on 1800 series and up. DC-Volt & DC-Amp optional on 1200 series for \$230 each.

ENGINE: Standard with world renown liquid cooled Kubota Diesel Engine.

UNDERCARRIAGE: 16" Pneumatic tires & tapered bearings. Brake available for \$369

SHIPPING DIMENSIONS: 65"L x 49"W x 54"H; approximately 1591-1599-1607-1615 lbs.

TERMS: Payment in full prior to shipping (deposit with order acceptable). Freight FOB origin (Wellston, OK USA). Lead time to be agreed upon when ordering. Price does not include shipping expenses (freight) and may change without notice, so please confirm when ordering.

EQUIPPED STANDARD WITH: 120/240 VAC household type power with engine running, & ability to power aircraft from hangar power without the engine running (DUAL POWERED).



BATESFIELD GPU
930335 S. Pilot Dr.
Wellston, OK 74881

Phone: 405-258-2600
sales@gasgpu.com
Fax: 405-258-3066
www.GasGPU.com

